

# Pyramid Industries Plenum Duct

**Applications:** Plenum, Riser and General Purpose Applications per Articles 770 and 800.

- UL Listed to 2024 Standard**
- Maximum flame propagation distance is less than 5.0 ft.
  - The peak optical density of smoke is less than 0.50
  - The average optical density of smoke is less than 0.15

## Standard Stock – Reels

	Color	Part No.	Nom. I.D.	Nom. O.D.	Pull Tape	Reel Size	Reel Length (ft.)
1"	White	PLM100T-1800	1.049	1.365	900 lb.	48-30-24	1800
	White	PLM100T-5000	1.049	1.365	900 lb.	72-41-24	5000
	White	PLM100T-8000	1.049	1.365	900 lb.	82-41-24	8000
1 1/4"	White	PLM125T-1000	1.250	1.550	900 lb.	48-30-24	1000
	White	PLM125T-5000	1.250	1.550	900 lb.	72-41-24	5000
	White	PLM125T-6000	1.250	1.550	900 lb.	82-41-24	6000
1 1/2"	White	PLM150T-2000	1.500	1.850	900 lb.	66-41-24	2000
	White	PLM150T-4000	1.500	1.850	900 lb.	82-41-24	4000
2"	White	PLM200T-2000	2.000	2.425	900 lb.	82-41-24	2000

## Standard Stock – Coils/Box

	Color	Part No.	Nom. I.D.	Nom. O.D.	Pull Tape	Box Size	Coil Length (ft.)
1"	White	PLM100T-250B2	1.049	1.365	900 lb.	34-14-34	250
1 1/4"	White	PLM125T-250B4	1.250	1.550	900 lb.	39-15-39	250
	White	PLM125T-500	1.250	1.550	900 lb.	-	500
1 1/2"	White	PLM150T-250B3	1.500	1.850	900 lb.	44-18-44	250

## Custom Orders

- \* Custom Orders are not returnable
- \* Custom lengths are available in minimum order quantities of 1000 ft.
- \* Custom color runs are available in minimum order quantities of 10,000 ft.

## Options:

- Size: 3/4"
- Split Duct
- Color: Black, Blue, Grey, Green, Red, Orange, Brown and Yellow
- Custom print line
- Two, three, or four way parallel

**Carlon**<sup>®</sup>  
LAMSON & SESSIONS

In USA, contact:  
25701 Science Park Drive ■ Cleveland, Ohio 44122  
1-800-3-CARLON (1-800-322-7566) ■ In Ohio, (216) 464-3400  
Fax: (216) 766-6444  
TDD/Hearing Impaired Access (216) 831-5918  
www.carlon.com

In Canada, contact:  
c/o Multimodal Logistics ■ 415 Traders Boulevard East  
Mississauga, Ontario ■ Canada L4Z 1P2  
(905) 755-1262 ■ (888) 269-9902  
Fax: (905) 755-1265 ■ (888) 229-8622