

## PRODUCT SPECIFICATIONS

| Size   | Nom. I.D. | Nom. O.D. | Pull Tape | Min. Bend Radius | Max Flame Rating | Storage      | Handling     | Wt./C ft. (lbs.) |
|--------|-----------|-----------|-----------|------------------|------------------|--------------|--------------|------------------|
| 3/4"   | .83"      | 1.04"     | Empty     | 2"               | UL 910           | -4°F – 158°F | -4°F – 104°F | 8                |
| 1"     | 1.05"     | 1.31"     | 900lb     | 3"               | UL 910           | -4°F – 158°F | -4°F – 104°F | 10               |
| 1 1/4" | 1.38"     | 1.65"     | 900lb     | 3"               | UL 910           | -4°F – 158°F | -4°F – 104°F | 16               |
| 1 1/2" | 1.55"     | 1.88"     | 900lb     | 4"               | UL 910           | -4°F – 158°F | -4°F – 104°F | 20               |
| 2"     | 2.04"     | 2.35"     | 900lb     | 4"               | UL 910           | -4°F – 158°F | -4°F – 104°F | 23               |

## PLENUM-GARD PART NUMBER SYSTEM

| Product         | Size       | Configuration  | Wall         | Color      | Pull Line             | Length                     |
|-----------------|------------|----------------|--------------|------------|-----------------------|----------------------------|
| C = Plenum-Gard | E = 3/4"   | 4 = Corrugated | X = Standard | 1 = Orange | C = 900 lb. Pull Tape | Example: -1000 = 1000 Feet |
|                 | F = 1"     |                |              | 4 = White  |                       | -1000S = 1000 Feet Split   |
|                 | G = 1 1/4" |                |              |            |                       |                            |
|                 | H = 1 1/2" |                |              |            |                       |                            |
|                 | J = 2"     |                |              |            |                       |                            |

**Note: Custom runs available in minimum order quantities of 1000 feet. Custom orders are NOT returnable.**

- For use per Articles 770 and 800 of the NEC
- UL Listed to UL910
- Outside Diameters meet IPS dimensions
- Available in standard or split configurations